

# IPC-7C13-IR3

## 1.3 megapixel IR waterproof Bullet IP

Camera



### FEATURES

- ℓ High resolution, Max resolution can reach 1.3MP(1280×960), HD 720P output, real-time image
- ℓ Low illumination, 0.1Lux @(F1.2, AGC ON), 0 LUX with IR
- ℓ Support Electronic switch Day and Night
- ℓ Local analog video output, support kinds of info overlay (ID, IP, DDNS server etc.)
- ℓ H.264 High Profile Compression
- ℓ Support Dual stream
- ℓ Support SDVR connection
- ℓ Support Cloud technology , One Step to realize remote surveillance, Remote Server add : [www.dvrcenter.net](http://www.dvrcenter.net)
- ℓ Support smart mobile and network (IE&Firefox&Safari&Chrome) real time remotely monitoring, such as iPhone, Blackberry, Android, Symbian and windows mobile
- ℓ Provide web, CMS and center manage software (MYEYE) and SDK for development
- ℓ Support connection with HVR/NVR, Compatible with ONVIF standard
- ℓ POE, alarm, audio and 3G & wifi optional



### SPECIFICATION

| Parameter          | 1.3 megapixel IR waterproof bullet IP Camera                                                    |
|--------------------|-------------------------------------------------------------------------------------------------|
| Camera             |                                                                                                 |
| Image Sensor       | 1/3" CMOS sensor                                                                                |
| Signal System      | PAL/NTSC                                                                                        |
| Effective Pixels   | 1280×960                                                                                        |
| Min. Illumination  | Color: 0.01Lux @(F1.2, AGC ON), 0 LUX with IR<br>B / W: 0.008Lux @(F1.2, AGC ON), 0 LUX with IR |
| Electronic Shutter | 1/50(1/60)s - 1/100,000 s                                                                       |
| LED                | 42pcs                                                                                           |

|                         |                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------|
| Lens                    | 6mm @ F1.2 (4mm/8mm optional)                                                                      |
| Lens Mount              | CS                                                                                                 |
| Day/Night               | Auto (Support IR-CUT)                                                                              |
| Synchronization way     | internal synchronization                                                                           |
| S/N Ratio               | > 48dB                                                                                             |
| Compression             |                                                                                                    |
| Video Compression       | H.264 High Profile, JPEG capture                                                                   |
| Video Bite Rate         | 100 Kbps~4Mbps                                                                                     |
| Image                   |                                                                                                    |
| Max Image Resolution    | 1280*960                                                                                           |
| Frame Rate              | 50Hz:25fps (1280*960)<br>60Hz:30fps (1280*960)                                                     |
| Image Setting           | Saturation,Brightness,Contrast adjustable through Client software or web server                    |
| Network Function        |                                                                                                    |
| Storage                 | NSA(Iscsi optional)                                                                                |
| Intelligent Alarm       | Motion detect, Video loss, Network disconnection, IP address conflict, Storage full, Storage error |
| Protocols               | TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP<br>(HTTPS, RTP/RTSP, SIP ,802.1x,IPv6 Optional)          |
| Basic                   | Anti-flicker,Dual stream,Heartbeat>Password protection                                             |
| Interface               |                                                                                                    |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet interface                                                   |
| Interface protocol      | ONVIF,PSIA,CGI                                                                                     |
| General                 |                                                                                                    |
| Operating Condition     | -10℃~60℃,Humidity 90% or less(non-condensing)                                                      |
| Ingress Protection      | IP66                                                                                               |

|                  |                |
|------------------|----------------|
| Power Supply     | DC12V±10%      |
| Power Comsuption | “IR2”:5W MAX;  |
| IR distance      | 30m            |
| Dimension(mm)    | L275*W93*H90mm |
| Weight(g)        | 267g           |