

IPC-9C13-IR4



1.3 megapixel IR waterproof Bullet IP

Camera



FEATURES

- ℓ High resolution, Max resolution can reach 1.3MP(1280×960), HD 720P output, real-time image
- ℓ Low illumination, 0.1Lux @(F1.2, AGC ON), 0 LUX with IR
- ℓ Support Electronic switch Day and Night
- ℓ Local analog video output, support kinds of info overlay (ID, IP, DDNS server etc.)
- ℓ H.264 High Profile Compression
- ℓ Support Dual stream
- ℓ Support SDVR connection
- ℓ Support Cloud technology , One Step to realize remote surveillance, Remote Server add : www.dvrcenter.net
- ℓ Support smart mobile and network (IE&Firefox&Safari&Chrome) real time remotely monitoring, such as iPhone, Blackberry, Android, Symbian and windows mobile
- ℓ Provide web, CMS and center manage software (MYEYE) and SDK for development
- ℓ Support connection with HVR/NVR, Compatible with ONVIF standard
- ℓ POE, alarm, audio and 3G & wifi optional



SPECIFICATION

| Parameter | 1.3 megapixel IR waterproof bullet IP Camera |
|--------------------|---|
| Camera | |
| Image Sensor | 1/3" CMOS sensor |
| Signal System | PAL/NTSC |
| Effective Pixels | 1280×960 |
| Min. Illumination | Color: 0.01Lux @(F1.2, AGC ON), 0 LUX with IR B / W: 0.008Lux @(F1.2, AGC ON), 0 LUX with IR |
| Electronic Shutter | 1/50(1/60)s - 1/100,000 s |
| LED | 36pcs |

| | |
|-------------------------|--|
| Lens | 6mm @ F1.2 (4mm/8mm optional) |
| Lens Mount | CS |
| Day/Night | Auto (Support IR-CUT) |
| Synchronization way | internal synchronization |
| S/N Ratio | > 48dB |
| Compression | |
| Video Compression | H.264 High Profile, JPEG capture |
| Video Bite Rate | 100 Kbps~4Mbps |
| Image | |
| Max Image Resolution | 1280*960 |
| Frame Rate | 50Hz:25fps (1280*960) 60Hz:30fps (1280*960) |
| Image Setting | Saturation,Brightness,Contrast adjustable through Client software or web server |
| Network Function | |
| Storage | NSA(Iscsi optional) |
| Intelligent Alarm | Motion detect, Video loss, Network disconnection, IP address conflict, Storage full, Storage error |
| Protocols | TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP (HTTPS, RTP/RTSP, SIP ,802.1x,IPv6 Optional) |
| Basic | Anti-flicker,Dual stream,Heartbeat>Password protection |
| Interface | |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet interface |
| Interface protocol | ONVIF,PSIA,CGI |
| General | |
| Operating Condition | -10°C~60°C,Humidity 90% or less(non-condensing) |
| Ingress Protection | IP66 |

| | |
|-------------------|------------------|
| Power Supply | DC12V±10% |
| Power Consumption | "IR2":5W MAX; |
| IR distance | 40m |
| Dimension(mm) | L270*W100*H138mm |
| Weight(g) | 267g |